

SPECIFICATIONS

TYPE	COOL & HEAT INVERTER	
INDOOR UNIT	ASYA07LCC	ASYA09LCC
OUTDOOR UNIT	AOYR07LCC	AOYR09LCC
COOLING CAPACITY	2.10 kW	2.60 kW
HEATING CAPACITY	3.00 kW	3.60 kW

ELECTRICAL DATA

POWER SOURCE		230 V	230 V
FREQUENCY		50 Hz	50 Hz
RUNNING CURRENT	COOLING	2.5 A	3.2 A
	HEATING	3.2 A	4.0 A
INPUT WATTS	COOLING	0.47 kW	0.655 kW
	HEATING	0.66 kW	0.845 kW
E.E.R.	COOLING	4.47 kW/kW	3.97 kW/kW
COP	HEATING	4.55 kW/kW	4.26 kW/kW
MOISTURE REMOVAL		1.0 L/hr	1.3 L/hr
AIR CIRCULATION -High	COOLING	595 m ³ /hr	595 m ³ /hr
	HEATING	645 m ³ /hr	645 m ³ /hr

COMPRESSOR

TYPE	Hermetic type, 4 pole, 3 phase, DC inverter motor, Rotary	
DISCRIMINATION	DA89X1C - 20FZ	
REFRIGERANT	R410A	900 g

FAN MOTOR

POWER SOURCE		230 V
INDOOR UNIT	HIGH-SPEED	Cool 1,300 / Heat 1,390 r.p.m.
	MED-SPEED	Cool 1,120 / Heat 1,200 r.p.m.
	LOW-SPEED	Cool 950 / Heat 1,000 r.p.m.
	QUIET	Cool 700 / Heat 760 r.p.m.
OUTDOOR UNIT		800 r.p.m.

DIMENSIONS

INDOOR UNIT	H x W x D	275 x 790 x 215 mm
OUTDOOR UNIT	H x W x D	540 x 660 x 290 mm

WEIGHT

INDOOR UNIT	GROSS / NET	12 / 9 kg
OUTDOOR UNIT	GROSS / NET	35 / 32 kg

NOISE LEVEL

INDOOR UNIT	High	Cool 41 dB / Heat 41 dB
	Med	Cool 36 dB / Heat 36 dB
	Low	Cool 30 dB / Heat 30 dB
	Quiet	Cool 21 dB / Heat 21 dB
OUTDOOR UNIT		Cool 47 dB / Heat 48 dB

REFRIGERANT (R410A)

	Pipe Length	15 m	900 g
FULL CHARGE AMOUNT		20 m	1,000 g
ADDITIONAL REFRIGERANT			20 g / m
MAXIMUM PIPING HEIGHT			15m